


NOTES

1. TIE DOWN FOR INSTALLATION WHERE THERE IS ACCESS TO THE DECKHEAD UNDERSIDE
2. SAFE WORKING LOAD (SWL) 44kN
3. *** INDICATES MIN ELEVATION WHEN THE M.O.D./NATO TIE DOWN LASHING END FITTINGS ARE EMPLOYED
4. TIE DOWN SHACKLE WILL ACCEPT TWO LASHING END FITTINGS SIMULTAINOUSLY
5. ROTATION ANGLE : CONTINUOUS
6. DRAIN HOLE THREAD 1/4 BSP PARALLEL IF A DRAIN IS REQUIRED A SUITABLE FITTING WITH A THREAD LENGTH OF 10mm OR LESS IS TO USED

							MATERIAL:	TITLE: LOAD ALIGNING HELICOPTER TIE DOWN PLATE UNDER DECK ACCESS BOLT IN	
							FINISH:		
2	OVERALL HEIGHT CORRECTED	JRC	22APRIL13				<p>NOTES: 1. TOLERANCE: +/- 0.25 UOS 2. SURFACE ROUGHNESS: 3.2mm UOS 3. REMOVE BURRS & SHARP EDGES 4. DO NOT SCALE</p>	FIRST USED ON: 2079	
1	CLEARED FOR PRODUCTION	JRC	11 MAY 10						
A	DRAWING INTRODUCED	KAG	1/SEPT/05			DRG No: ASSY 2080 SHEET 2			
ISS	CHANGE	DRAWN	DATE	CHECKED	DATE				

NOTES:

1. TOLERANCE: +/- 0.25 UOS
2. SURFACE ROUGHNESS: 3.2mm UOS
3. REMOVE BURRS & SHARP EDGES
4. DO NOT SCALE